

Milling motor FM 800

NEW



Highest concentricity due to delicate adjustment of all components, such as the double-bearing spindle for absorbing axial forces and the innovative, tool-free quick-clamping device.



The sound pressure level of the FM 800 is only 71 db (A) and the device is thus.



The MAFELL milling motors are manufactured under the strictest quality controls in the German town of Oberndorf a. N. Before delivery, each milling motor is "run in" in a test cabin. This increases the tool life and the service life.

Product features

- **Extremely quiet**
- **Spindle lock**
- **Made in Germany**
- **LED indication for overload**

Areas of application

- Model making, mould making, advertising technology, engraving, jewellery, electronics, stonemasonry
- Ideally suited for portal milling machines, cutting tables, grinding devices and flexible shafts
- For wood, metal, plastics, foam, polystyrene, stone

Product description

With the FM 800, MAFELL has developed another milling motor "Made in Germany". The high quality standard and well thought-out details make the MAFELL milling motor the best partner in its performance class.

The speed can be infinitely adjusted to any application. In addition, the digital electronics are equipped with soft start, constant speed under load, idle speed reduction and overload protection.

The labyrinth seal of FM 800 permanently protects the spindle and bearing from even the smallest particles, dust and chips.

Your MAFELL dealer - our sales partner:

Technical data

FM 800

Nominal power consumption	800 W
Universal motor	230 V / 50 Hz
Nominal idling speed	7.000 – 25.000 rpm
Clamping collar / collet chuck	43 mm (1,69 in.) / 6 mm (0,31 in.)
Dimensions (L x W x H)	254 x 79 x 73 mm (10 x 3,11 x 2,87 in.)
Sound pressure level db (A)	71 dB (A)
Weight	1,65 kg (3,64 lbs)

Models

Milling motor FM 800	9M0010
-----------------------------	---------------

Scope of supply

- 1 collet chuck OZ 6 mm (0,31 in.)
- 1 spanner
- 1 cable 1 m

Special accessories / tools

Union nut	093729
Collet chuck OZ 3 mm	093731
Collet chuck OZ 4 mm	093732
Collet chuck OZ 6 mm	093733
Collet chuck OZ 8 mm	093734
Collet chuck OZ 3,175 mm (1/8")	093735
Collet chuck OZ 6,35 mm (1/4")	093736
Collet chucks-set OZ 3 mm*	093737
Collet chucks-set OZ 3,175 mm (1/8")*	093738

* (consisting of collet chuck and union nut)